

## DECLARATION OF PERFORMANCE

No. CPR\_01

1. Unique identification code of the product type: **Dry-pressed ceramic tiles, with water absorption Eb ≤ 0,5 %**
2. Intended uses: **For internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer: **Ceramiche Keope, S.S. 467 n° 21 42013 Casalgrande (RE) ITALY**
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 <sub>FL</sub> /A1	EN 14411:2012
Release of dangerous substance (only for GL ceramic tiles):		
- Cadmium	npd	
- Lead	npd	
Breaking strength (thickness ≥ 7,5)	≥ 1300 N	
Breaking strength (thickness < 7,5)	≥ 700 N	
Slipperiness	See table attached	
Tactility	npd	
Bond strength/adhesion	npd	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

*Davide Mussini – Managing Director*

.....  
 Name and function



Casalgrande (RE) Italy, 08/10/2018

.....  
 Place, date

.....  
 Signature

**Table - Slipperiness rev. 08/10/2018**

NOTE	DIN 51130 (DE)	BCRA D.M. 236/1989 (ITA)
CHORUS TOBACCO R9	R9	> 0,40
CHORUS SILVER R9		
CHORUS BEIGE R9		
CHORUS GREY R9		
CHORUS WHITE R9		
CHORUS TOBACCO R10	R10	> 0,40
CHORUS SILVER R10		
CHORUS BEIGE R10		
CHORUS GREY R10		
CHORUS WHITE R10		
CHORUS TOBACCO R11	R11	> 0,40
CHORUS SILVER R11		
CHORUS BEIGE R11		
CHORUS GREY R11		
CHORUS WHITE R11		