

FORMATI / SIZES










	120x120 48"x48"	60x120 24"x48"	30x120 12"x48"	75x75 30"x30"	37,5x75 15"x30"	60x60 24"x24"	30x60 12"x24"	9,7x60 3,9"x24"	60x120 24"x48"	60x60 24"x24"	30x60 12"x24"
	1194x1194	596x1195	397x1195	748x748	373x748	596x596	297x596	97x596	596x1195	596x596	297x596
	RT	RT	RT	RT	RT	RT	RT	RT	RT	RT	RT
	9 mm	9 mm	9 mm	9,5 mm	9,5 mm	9 mm	9 mm	9mm	K2 20 mm	K2 20 mm	K2 20 mm
CHORUS TOBACCO	●	● ■ ▲	●	●	●	● ■ ▲	● ■ ▲	●	▲	▲	▲
CHORUS SILVER	●	● ■ ▲	●	●	●	● ■ ▲	● ■ ▲	●	▲	▲	▲
CHORUS BEIGE	●	● ■ ▲	●	●	●	● ■ ▲	● ■ ▲	●	▲	▲	▲
CHORUS GREY	●	● ■ ▲	●	●	●	● ■ ▲	● ■ ▲	●	▲	▲	▲
CHORUS WHITE	●	● ■ ▲	●	●	●	● ■ ▲	● ■ ▲	●	▲	▲	▲

● Natural R9 | ■ Grip R10 | ▲ Grip R11

MISURE, PESI ED IMBALLI / SIZE, WEIGHT AND PACKAGING

FORMATO SIZE	SPESSORE THICKNESS	PZ/SCATOLA PIECES/BOX	MQ/SCATOLA SQM/BOX	KG/SCATOLA KG/BOX	MQ/PALLET SQM/PALLET	KG/PALLET KG/PALLET	SCATOLA/PALLET BOX/PALLET
120x120	9 mm	2	2,86	≅ 60,75	57,12	≅ 1228	20
60x120	9 mm	2	1,44	≅ 27,56	21,60	≅ 426,40	15
30x120	9 mm	4	1,44	≅ 31,48	23,04	≅ 516,68	16
75x75	9,5 mm	2	1,13	≅ 26,00	47,25	≅ 1105	42
37,5x75	9,5 mm	4	1,13	≅ 25,94	27,00	≅ 635,56	24
60x60	9 mm	3	1,08	≅ 24,00	43,20	≅ 973	40
30x60	9 mm	6	1,08	≅ 23,80	43,20	≅ 965	40
9,7x60	9 mm	10	0,58	≅ 13,00	34,92	≅ 793	60
60x120 K2	20 mm	1	0,72	≅ 33,75	10,80	≅ 519,25	15
60x60 K2	20 mm	2	0,72	≅ 32,90	21,60	≅ 1000	30
30x60 K2	20 mm	3	0,54	≅ 24,67	21,60	≅ 999,80	40

INFORMAZIONI TECNICHE / TECHNICAL FEATURES

INFORMAZIONI TECNICHE TECHNICAL FEATURES	NORMA NORM EN 14411 - ISO 13006	REQUISITI PRESCRITTI REQUIRED VALUES	VALORI VALUES
 DIMENSIONI RETTIFICATO SIZES RECTIFIED	UNI EN ISO 10545-2	lunghezza-larghezza / length-width ±0,3% (±1,0 mm max) spessore / thickness ±0,5% (±0,5 mm max) ortogonalità / rectangularity ±0,3% (±1,5 mm max) rettilinearità / straightness ±0,3% (±0,8 mm max) planarità / flatness ±0,4% (±1,8 mm max) qualità superficie / surface quality ≥95%	CONFORME COMPLIANT
 ASSORBIMENTO ACQUA WATER ABSORPTION	UNI EN ISO 10545-3	≤0,5%	≤0,1%
 RESISTENZA A ROTTURA BREAKING STRENGTH	UNI EN ISO 10545-4	R≥35 N/mm ² S≥700 N (<7,5 mm) S≥1300 N (≥7,5 mm)	CONFORME COMPLIANT
 RESISTENZA ABRASIONE PROFONDA (UGL - Matt) DEEP ABRASION RESISTANCE (UGL - Matt)	UNI EN ISO 10545-6	≤175 mm ³	≤150 mm ³
 RESISTENZA SHOCK TERMICI THERMAL SHOCK RESISTANCE	UNI EN ISO 10545-9	resistenza / resistant	CONFORME COMPLIANT
 RESISTENZA AL GELO FROST RESISTANCE	UNI EN ISO 10545-12	resistenza / resistant	CONFORME COMPLIANT
 RESISTENZA CHIMICA CHEMICAL RESISTANCE	UNI EN ISO 10545-13	resistenza / resistant	CONFORME COMPLIANT
 RESISTENZA ALLE MACCHIE RESISTANCE TO STAINS	UNI EN ISO 10545-14	pulibile / cleanable	CONFORME COMPLIANT
	DIN 51130	R	prodotto / product
			R >0,40 >0,42
	B.C.R.A. (COF)	>0,40 bagnato / wet	120x120 - 60x120 - 30x120 - 75x75 - 37,5 x 75 - 60x60 - 30x60 - 9,7x60
 CLASSIFICAZIONE ALTISDRUCCIOLO ASSESSMENT OF SLIP RESISTANCE			R9 CONFORME COMPLIANT
			60x120 - 60x60 - 30x60
	ANSI A137.1 2012 (DCOF)	>0,42 bagnato / wet	60x120 K2 - 60x60 K2 - 30x60 K2
			R10 CONFORME COMPLIANT
			R11 CONFORME COMPLIANT

Piastrelle pressate a secco - Conforme alla norma EN 14411 e ISO 13006 appendice G gruppo B1-a con E ≤0,5%
Dry pressed tiles - Compliant with standards EN 14411 and ISO 13006 annex G group B1-a with E ≤0,5%