












DESCRIZIONE <i>DESCRIPTION / DESCRIPTION BESCHREIBUNG / DESCRIPCIÓN</i>	NORME <i>REGULATION NORME / NORM NORMA</i>	REQUISITI PRESCRITTI <i>REQUIRED VALUES / EXIGENCES RÉGLEMENTAIRES / VORGESCHRIEBENE ANFORDERUNGEN / REQUISITOS ESTABLECIDOS</i>	VALORI <i>VALUES / VALEURS WERTE / VALORES</i>
	EN 14411 - ISO 13006		VIEW
 DIMENSIONI RETTIFICATO <i>SIZES RECTIFIED / FORMAT RECTIFIÉ / ABMESSUNGEN NACH DEM SCHLEIFEN / TAMAÑO RECTIFICADO</i>	UNI EN ISO 10545-2	lunghezza-larghezza ±0,3% (±1,0 mm max) <i>length-width / longueur-largeur / Länge-Breite / longitud-ancho</i>	CONFORME <i>COMPLIANT / CONFORME ANFORDERUNGEN ERFÜLLT / CONFORME</i>
		spessore ±5,0% (±0,5 mm max) <i>thickness / épaisseur / Stärke / espesor</i>	
		ortogonalità ±0,3% (±1,5 mm max) <i>rectangularity / orthogonalité / Rechtwinkligkeit / ortogonalidad</i>	
		rettilinearità ±0,3% (±0,8 mm max) <i>straightness / rectilignité / Geradlinigkeit / rectilineidad</i>	
		planarità ±0,4% (±1,8 mm max) <i>surface flatness / planéité / Ebenflächigkeit / planaridad</i>	
		qualità superficie ≥95% <i>surface quality / qualités surface / Oberflächenbeschaffenheit cualidades superficie</i>	
		lunghezza-larghezza ±0,6% (±2,0 mm max) <i>length-width / longueur-largeur / Länge-Breite / longitud-ancho</i>	
		spessore ±5,0% (±0,5 mm max) <i>thickness / épaisseur / Stärke / espesor</i>	
		ortogonalità ±0,5% (±2,0 mm max) <i>rectangularity / orthogonalité / Rechtwinkligkeit / ortogonalidad</i>	
		rettilinearità ±0,5% (±1,5 mm max) <i>straightness / rectilignité / Geradlinigkeit / rectilineidad</i>	
 DIMENSIONI NON RETTIFICATO <i>SIZES NOT RECTIFIED / FORMAT RECTIFIÉ / ABMESSUNGEN VOR DEM SCHLEIFEN / TAMAÑO NO RECTIFICADO</i>	UNI EN ISO 10545-2	planarità ±0,5% (±2,0 mm max) <i>surface flatness / planéité / Ebenflächigkeit / planaridad</i>	—
		qualità superficie ≥95% <i>surface quality / qualités surface / Oberflächenbeschaffenheit cualidades superficie</i>	
 ASSORBIMENTO ACQUA <i>WATER ABSORPTION / ABSORPTION D'EAU WASSERAUFNAHME / ABSORCIÓN DE AGUA</i>	UNI EN ISO 10545-3	≤0,5%	≤0,1%
 RESISTENZA A ROTTURA <i>BREAKING STRENGHT / RÉSISTANCE À LA RUPTURE / BRUCHFESTIGKEIT / RESISTENCIA A LA ROTURA</i>	UNI EN ISO 10545-4	R≥35 N/mm² S≥700 N (<7,5 mm) S≥1300 N (≥7,5 mm)	CONFORME <i>COMPLIANT / CONFORME ANFORDERUNGEN ERFÜLLT / CONFORME</i>
 RESISTENZA ABRASIONE PROFONDA (UGL - Matt) <i>DEEP ABRASION RESISTANCE (UGL - Matt) / RÉSISTANCE À L'ABRASION PROFONDE (UGL - Matt) / TIEFENVERSCHLEISSBESTÄNDIGKEIT (UGL - Matt) / RESISTENCIA A LA ABRASIÓN PROFUNDA (UGL - Matt)</i>	UNI EN ISO 10545-6	≤175 mm³	≤150 mm³
 RESIST. ABRASIONE SUPERFICIALE (GL - Lappato) <i>SURFACE ABRASION RESISTANCE (GL - Lappato) / RÉSIST. À L'ABRASION SUPERFICIELLE (GL - Rodé) / WIDERSTÄNDIGKEIT GEGEN OBERFLÄCHENVERSCHLEISS (GL - geläppt) / RESIST. ABRASIÓN SUPERFICIAL (GL: esmaltado)</i>	UNI EN ISO 10545-6	dichiarare un valore / declare a value / déclarer une valeur / — <i>Einen Wert angeben / declarar un valor</i>	
 RESISTENZA SHOCK TERMICI <i>THERMAL SHOCK RESISTANCE / RÉSISTANCE AUX ÉCARTS DE TEMPÉRATURE / WIDERSTANDSFÄHIGKEIT GEGEN TEMPERATURSCHWANKUNGEN / RESISTENCIA A LOS CAMBIOS DE TEMPERATURA</i>	UNI EN ISO 10545-9	resistenza / resistant / résistance / Widerständigkeit / <i>resistencia</i>	CONFORME <i>COMPLIANT / CONFORME ANFORDERUNGEN ERFÜLLT / CONFORME</i>
 RESISTENZA AL GELO <i>FROST RESISTANCE / RÉSISTANCE AU GEL / FROSTWIDERSTANDSFÄHIGKEIT / RESISTENCIA AL HIELO</i>	UNI EN ISO 10545-12	resistenza / resistant / résistance / Widerständigkeit / <i>resistencia</i>	CONFORME <i>COMPLIANT / CONFORME ANFORDERUNGEN ERFÜLLT / CONFORME</i>
 RESISTENZA CHIMICA <i>CHEMICAL RESISTANCE RÉSISTANCE CHIMIQUE CHEMISCHE BESTÄNDIGKEIT RESISTENCIA QUÍMICA</i>	UNI EN ISO 10545-13	resistenza / resistant / résistance / Widerständigkeit / <i>resistencia</i>	CONFORME <i>COMPLIANT / CONFORME ANFORDERUNGEN ERFÜLLT / CONFORME</i>
 RESISTENZA ALLE MACCHIE <i>STAIN RESISTANCE / RÉSISTANCE AUX TACHES / FLECKENFESTIGKEIT / RESISTENCIA A LAS MANCHAS</i>	UNI EN ISO 10545-14	pulibile / cleanable / nettoyable / Kann gereinigt werden / <i>lavable</i>	CONFORME <i>COMPLIANT / CONFORME ANFORDERUNGEN ERFÜLLT / CONFORME</i>
 CLASSIFICAZIONE ANTISDRUCCIOLO <i>ASSESSMENT OF SLIP RESISTANCE / CLASSIFICATION ANTIGLISSE RUTSCHFESTIGKEITSKLASSECLASIFICACIÓN ANTIDESLIZANTE</i>	DIN 51130	R	R9 60x60 - 30x60 R11 60x60 K2
	DIN 51097	A+B+C	A Natural R9 / A+B+C Structured R11
	B.C.R.A. (COF)	>0,40 bagnato / wet	CONFORME <i>COMPLIANT / CONFORME ANFORDERUNGEN ERFÜLLT / CONFORME</i>
	ANSI A137.1 2012 (DCOF)	>0,42 bagnato / wet	CONFORME <i>COMPLIANT / CONFORME ANFORDERUNGEN ERFÜLLT / CONFORME</i>